



Flexitank Europe Bvba

Primeurstraat 15- 2100 Deurne-Antwerpen

Tel +32 (0)3.314.88.01

Fax +32 (0)3.366.16.90

Email info@flexitankeurope.be

URL www.flexitankeurope.be

Container Specification

The following document is an abridged version of the full container specification, listing the main points that need to be adhered to when selecting a container. This document does not replace the container specification but should be used as a quick reference guide to cover the main requirements listed in the full specification.

- 3 years old or less (check manufacturers label plate)
- 30 ton rating
- Full side wall corrugation (90 degree wherever possible) – Absolutely no decal or marker panels
- Vertical recess in rear corner post assemblies to accept bulkhead-fixing bolts.
- 2 fully operative locking bars on each door
- A minimum of 5 lashing rings along the base of each side wall assembly, each ring having a working load capacity of 2000 KG. The rings shall be located within 30 cm of end walls/doors.
- No hazardous cargo warning labels
- Container free from holes, debris, sharp edges, burrs, floor splinters or loose floor screws, dents or any such welds or similar repair on the inside surfaces of the container that may cause damage to the flexitank
- All interior surfaces to be free from stains and sources of contamination which may damage the flexitank material or leach into the liquid cargo

Any container not meeting the above standards requires the approval from Flexitank Europe prior to use.